

Right Angle SMA Plug to Right Angle SMA Plug

Type	Cable Dia.	Length	Item #	1-9	10-24	25-99	100+
RG174/U Center Conductor: 26 AWG bare copper covered steel Min. Bend Radius: 0.47" (12mm) Jacket: Black PVC Operating Temperature: -40°C - +75°C	.110in. (2.8mm)	0.5ft (0.15m)	CC174S-05HR2	28.10	26.41	24.73	CALL
		1.0ft (0.3m)	CC174S-1HR2	28.25	26.56	24.86	CALL
		1.5ft (0.45m)	CC174S-1.5HR2	28.45	26.74	25.04	CALL
		2.5ft (0.75m)	CC174S-2.5HR2	28.75	27.03	25.30	CALL
		5.0ft (1.5m)	CC174S-5HR2	29.55	27.78	26.00	CALL
RG188A/U Center Conductor: 26 AWG silver coated copper covered steel Min. Bend Radius: 0.50" (12.7mm) Jacket: White TFE taped Operating Temperature: -70°C - +200°C	.108in. (2.7mm)	1.0ft (0.3m)	CCSR188A-1	21.60	20.74	19.87	CALL
		1.5ft (0.45m)	CCSR188A-1.5	22.15	21.26	20.38	CALL
		2.0ft (0.6m)	CCSR188A-2	22.70	21.79	20.88	CALL
		2.5ft (0.75m)	CCSR188A-2.5	23.25	22.32	21.39	CALL
		3.0ft (0.9m)	CCSR188A-3	23.80	22.85	21.90	CALL
RG316/U Center Conductor: 26 AWG silver coated copper covered steel Min. Bend Radius: 0.51" (13mm) Jacket: Brown FEP Operating Temperature: -70°C - +200°C	.098in. (2.5mm)	4.0ft (1.2m)	CCSR188A-4	24.85	23.86	22.86	CALL
		1.0ft (0.3m)	CCSR316-1	21.60	20.74	19.87	CALL
		1.5ft (0.45m)	CCSR316-1.5	22.15	21.26	20.38	CALL
		2.0ft (0.6m)	CCSR316-2	22.70	21.79	20.88	CALL
		2.5ft (0.75m)	CCSR316-2.5	23.25	22.32	21.39	CALL
RG58C/U Center Conductor: 20 AWG tinned copper Min. Bend Radius: 2.00" (50.8mm) Jacket: Black PVC Operating Temperature: -40°C - +85°C	.195in. (5.0mm)	3.0ft (0.9m)	CCSR316-3	23.80	22.85	21.90	CALL
		0.5ft (0.15m)	CCS58A-05HR2	19.15	18.00	16.85	CALL
		1.0ft (0.3m)	CCS58A-1HR2	19.30	18.14	16.98	CALL
		1.5ft (0.45m)	CCS58A-1.5HR2	19.45	18.28	17.12	CALL
		2.5ft (0.75m)	CCS58A-2.5HR2	19.65	18.47	17.29	CALL
		5.0ft (1.5m)	CCS58A-5HR2	20.60	19.36	18.13	CALL
		10.0ft (3.0m)	CCS58A-10HR2	22.20	20.87	19.54	CALL

Inline SMA Plug to Inline BNC Plug

Type	Cable Dia.	Length	Item #	1-9	10-24	25-99	100+
RG174/U Center Conductor: 26 AWG bare copper covered steel Min. Bend Radius: 0.47" (12mm) Jacket: Black PVC Operating Temperature: -40°C - +75°C	.110in. (2.8mm)	0.5ft (0.15m)	CC174SB-05	15.15	14.24	13.33	CALL
		1.0ft (0.3m)	CC174SB-1	15.30	14.38	13.46	CALL
		1.5ft (0.45m)	CC174SB-1.5	15.45	14.52	13.60	CALL
		2.5ft (0.75m)	CC174SB-2.5	15.80	14.85	13.90	CALL
		5.0ft (1.5m)	CC174SB-5	16.60	15.60	14.61	CALL
RG58C/U Center Conductor: 20 AWG tinned copper Min. Bend Radius: 2.00" (50.8mm) Jacket: Black PVC Operating Temperature: -40°C - +85°C	.195in. (5.0mm)	10.0ft (3.0m)	CC174SB-10	18.20	17.11	16.02	CALL
		1.0ft (0.3m)	CCS58AB-1	13.40	12.60	11.79	CALL
		1.5ft (0.45m)	CCS58AB-1.5	13.60	12.78	11.97	CALL
		2.5ft (0.75m)	CCS58AB-2.5	13.90	13.07	12.23	CALL
		5.0ft (1.5m)	CCS58AB-5	14.70	13.82	12.94	CALL
		7.5ft (2.3m)	CCS58AB-7.5	15.50	14.57	13.64	CALL
		10ft (3.0m)	CCS58AB-10	16.35	15.37	14.39	CALL

Inline BNC Plug to Inline BNC Plug

Type	Cable Dia.	Length	Item #	1-9	10-24	25-99	100+
RG174/U Center Conductor: 26 AWG bare copper covered steel Min. Bend Radius: 0.47" (12mm) Jacket: Black PVC Operating Temperature: -40°C - +75°C	.110in. (2.8mm)	1.0ft (0.3m)	CC174-1	7.60	7.14	6.69	CALL
		1.5ft (0.45m)	CC174-1.5	7.75	7.29	6.82	CALL
		2.5ft (0.75m)	CC174-2.5	8.05	7.57	7.08	CALL
		5.0ft (1.5m)	CC174-5	8.90	8.37	7.83	CALL
		7.5ft (2.3m)	CC174-7.5	9.70	9.12	8.54	CALL
RG58C/U Center Conductor: 20 AWG tinned copper Min. Bend Radius: 2.00" (50.8mm) Jacket: Black PVC Operating Temperature: -40°C - +85°C	.195in. (5.0mm)	25.0ft (7.6m)	CC174-25	15.35	14.43	13.51	CALL
		1.0ft (0.3m)	CC58C-1	7.90	7.43	6.95	CALL
		2.5ft (0.75m)	CC58C-2.5	8.40	7.90	7.39	CALL
		2.0ft (0.6m)	CC58C-5	9.20	8.65	8.10	CALL
		2.5ft (0.75m)	CC58C-10	10.80	10.15	9.50	CALL
RG58/U ThinNet Plenum Center Conductor: 20 AWG tinned copper Min. Bend Radius: 2.00" (50.8mm) Jacket: Beige PVC Operating Temperature: -40°C - +75°C	.185in. (4.7mm)	3.0ft (0.9m)	CC58C-15	12.45	11.70	10.96	CALL
		4.0ft (1.2m)	CC58C-50	23.80	22.37	20.94	CALL
		1.0ft (0.3m)	CCTN58P-1B	17.30	16.61	15.92	CALL
		2.5ft (0.75m)	CCTN58P-2.5B	19.45	18.67	17.89	CALL
		5.0ft (1.5m)	CCTN58P-5B	24.85	23.86	22.86	CALL
RG223/U Center Conductor: 19 AWG solid silver coated copper Min. Bend Radius: 0.98" (25mm) Jacket: Black PVC Operating Temperature: -40°C - +60°C	.212in. (5.4mm)	7.5ft (2.3m)	CCTN58P-7.5B	29.20	28.03	26.86	CALL
		10.0ft (3.0m)	CCTN58P-10B	33.50	32.16	30.82	CALL
		50.0ft (15.2m)	CCTN58P-50B	94.00	90.24	86.48	CALL
		1.0ft (0.3m)	CC223B-1	21.10	20.26	19.41	CALL
		1.5ft (0.45m)	CC223B-1.5	21.90	21.02	20.15	CALL
RG142B/U Center Conductor: 18 AWG solid silver coated copper Min. Bend Radius: 0.98" (25mm) Jacket: Brown FEP Operating Temperature: -70°C - +200°C	.195in. (5.0mm)	2.5ft (0.75m)	CC223B-2.5	23.50	22.56	21.62	CALL
		5.0ft (1.5m)	CC223B-5	27.55	26.45	25.35	CALL
		10.0ft (3.0m)	CC223B-10	35.65	34.22	32.80	CALL
		15.0ft (4.6m)	CC223B-15	43.75	42.00	40.25	CALL
		1.0ft (0.3m)	CC142B-1	16.05	15.41	14.77	CALL
RG213/U Center Conductor: 13 AWG bare copper Min. Bend Radius: 1.57" (40mm) Jacket: Black PVC Operating Temperature: -40°C - +80°C	.405in. (10.3mm)	2.5ft (0.75m)	CC142B-2.5	18.65	17.90	17.16	CALL
		5.0ft (1.5m)	CC142B-5	22.95	22.03	21.11	CALL
		7.5ft (2.3m)	CC142B-7.5	27.30	26.21	25.12	CALL
		10.0ft (3.0m)	CC142B-10	31.60	30.34	29.07	CALL
		50.0ft (15.2m)	CC142B-50	100.75	96.72	92.69	CALL
		5.0ft (1.5m)	CC213B-5	18.90	18.14	17.39	CALL
		10.0ft (3.0m)	CC213B-10	22.95	22.03	21.11	CALL
		15.0ft (4.6m)	CC213B-15	27.00	25.92	24.84	CALL
		25.0ft (7.6m)	CC213B-25	35.10	33.70	32.29	CALL
		50.0ft (15.2m)	CC213B-50	55.35	53.14	50.92	CALL
		100.0ft (30.5m)	CC213B-100	95.85	92.02	88.18	CALL

